

Protection Device	Rated Voltage	Short-Circuit Current [kA]	Starter Type	Coordination Type	Overload Relay	Motor Rated Power [kW]/[HP]
All	All	All	All	All	All	Overview
ACB	240Vac	3	DOL-NS	IEC Type 1	Embedded	0
Fuses	400Vac	5	DOL-HD	IEC Type 2	TOL	0.06
MCCB	415Vac	10	SD-NS	UL Type A	EOL	0.09
MMS	440Vac	12	SS-NS-IL	UL Type C	UMC	0.12
	460Vac	16	SS-NS-ID	UL Type D		0.18
	480Vac	18	UL	UL Type E		0.25
	500Vac	20		UL Type F		0.37
	525Vac	22		UL Component		0.5
	600Y/347Vac	25				0.55
	600Vac	27				0.75
	690Vac	30				1
	1000Vac	35				1.1
		36				1.5

8 records. (0.17 seconds)

Show newest ABB products only  | Number of Records to show : 20

The closest tables matching your search are shown (Current Smart Search is on)

**MCCB, 400 Vac, 35 kA, DOL-NS, Coordination Type IEC Type 2, Overload Relay TOL**

Motor		Moulded Case Circuit Breakers		Contactor	Overload Relay
Rated Power [kW]	Rated Current [A]	Type	Instantaneous Tripping Current [A]	Type	Type
18.50	35.00	XT2N 160 MA 52	520.00	A50	TA75DU42
18.50	35.00	XT2N 160 MA 52	520.00	AF40	TA42DU-42 **

**MCCB, 400 Vac, 50 kA, DOL-NS, Coordination Type IEC Type 2, Overload Relay TOL**

Motor		Moulded Case Circuit Breakers		Contactor	Overload Relay
Rated Power [kW]	Rated Current [A]	Type	Instantaneous Tripping Current [A]	Type	Type
18.50	35.00	XT2S 160 MA 52	520.00	AF40	TA42DU-42 **
18.50	35.00	XT2S 160 MA 52	520.00	A50	TA75DU42

**MCCB, 400 Vac, 70 kA, DOL-NS, Coordination Type IEC Type 2, Overload Relay TOL**

Motor		Moulded Case Circuit Breakers		Contactor	Overload Relay
Rated Power [kW]	Rated Current [A]	Type	Instantaneous Tripping Current [A]	Type	Type

Motor		Moulded Case Circuit Breakers		Contactor	Overload
Rated Power [kW]	Rated Current [A]	Type	Instantaneous Tripping Current [A]	Type	Current
18.50	35.00	XT2H 160 MA 52	520.00	AF40	TA42DU-42 **

MCCB, 400 Vac, 85 kA, DOL-NS, Coordination Type IEC Type 2, Overload Relay TOL

Motor		Moulded Case Circuit Breakers		Contactor	Overload
Rated Power [kW]	Rated Current [A]	Type	Instantaneous Tripping Current [A]	Type	Current
18.50	35.00	XT2L 160 MA 52	520.00	A50	TA75DU42

MCCB, 400 Vac, 100 kA, DOL-NS, Coordination Type IEC Type 2, Overload Relay TOL

Motor		Moulded Case Circuit Breakers		Contactor	Overload
Rated Power [kW]	Rated Current [A]	Type	Instantaneous Tripping Current [A]	Type	Current
18.50	35.00	T4L250 PR221-I In100	450.00	A95	UMC22/UMC100

[▲ Top](#)

The data are not binding.  
 ABB reserves the right to modify the content of this document on the basis of technical development of the products, without prior notice.  
 Copyright 2012 ABB. All rights reserved.



Power and productivity  
 for a better world™